

VERSTEE

== LEATHER ==

TECHNISCHE FICHE

ARTIKELNAAM	PRAXIS KUNSTLEDER
PRODUCTIE	DUITSLAND
ROLBREEDTE	137-140 CM
DIKTE	Ca 1,1 MM
ROLLENGTE	25 M

TEST	TEST METHOD	RESULT
PHYSICAL		
Weight	DIN 53352	Ca. 600 gr/m ²
Composition	Coating	PVC
	Backing	Polyester, katoen
STRENGTH		
Martindale	BS 5690	≥100.000 cycles
Tear strength	DIN 53356 Warp	≥ 18 N
	Weft	≥ 15 N
Tensile strength	DIN 53354 Warp	≥ 280 N
	Weft	≥ 130 N
Needle tear strength	DIN 53506 Warp	≥ 30 N
	Weft	≥ 40 N
Adhesion	DIN 53357 Warp	≥ 30 N/5 cm
	Weft	≥ 40 N/5 cm
Elongation	DIN 53354 Warp	≥ 30%
	Weft	≥ 150%
Colour fastness to light	DIN EN ISO 105-B02	≥ 6 (blue scale)
Colour fastness to abrasion	DIN EN ISO 2015-A02 Dry & Wet (200 cm)	≥4

VERSTEE

== LEATHER ==

SAFETY		
Flame retardant UK	EN 1021, 1 & 2	Passed
Flame retardant US	FMVSS 302	Passed
Resistance to flexing at -10°C	DIN 53359	≥ 5.000
Resistance to flexing	DIN 53359	≥ 50.000
Resistance to water penetration		≥ 200 cm
Flame retardant IMO	A652 (16)	Passed
SAFETY		
Reach	Free of harmful substances	Complies
Free of phthalates		Complies