

VERSTEE

== LEATHER ==

TECHNISCHE FICHE

ARTIKELNAAM	COAST KUNSTLEDER
PRODUCTIE	DUITSLAND
ROLBREEDTE	140 CM
DIKTE	Ca 0,95 MM
ROLLENGTE	30 M

TEST	TEST METHOD	RESULT
PHYSICAL		
Weight	DIN EN ISO 2286	Ca. 565 gr/m ²
Composition	Coating	88% PVC compound
	Backing	12% polyester
STRENGTH		
Martindale	DIN EN ISO 5470-2	≥150.000 cycles
Tear strength	DIN EN ISO 4674-1	
	Warp	≥ 24 N
	Weft	≥ 30 N
Tensile strength	DIN EN ISO 1421	
	Warp	≥ 350 N
	Weft	≥ 300 N
Adhesion	DIN EN ISO 2411	
	Warp	≥ 30 N/5 cm
	Weft	≥ 30 N/5 cm
Elongation	DIN EN ISO 1421	
	Warp	≥ 150%
	Weft	≥ 180%
Colour fastness to light	DIN EN ISO 105-B02	≥ 6 (blue scale)
Colour fastness to rubbing	DIN EN ISO 105-X12 Dry&Wet	4-5
Colour fastness to chlorinated water	DIN EN ISO 105-E03	4-5 (grey scale)
Colour fastness to salt water	DIN EN ISO 105-E02	4-5 (grey scale)
Resistance to alcohol <96%	ISO 25647	Passed

VERSTEE

== LEATHER ==

SAFETY		
Flame-retardant (UK)	EN 1021, 1&2	Passed
Flame-retardant (IMO)	MSC.307 (88), Annex 1 Part 8	Passed
Resistance to bacteria	JIS Z 2801	Passed
Resistance to fungi	ISO 846	Passed
Resistance to hydrostatic pressure		1808 cm/H2O
SAFETY		
Animal Free	Free of animal derivated materials	Complies