

VERSTEE

== LEATHER ==

TECHNISCHE FICHE

ARTIKELNAAM	JUSTA
PRODUCTIE	SLOVENIE
ROLBREEDTE	142 CM
ROLLENGTE	30-40M

TEST	TEST METHOD	RESULT
PHYSICAL		
Weight		Ca. 610 gr/m ²
Composition	Coating	100% polyester
	Backing	100% polyester
STRENGTH		
Martindale	EN ISO 12947-1,2	≥ 65.000 cycles
Tear strength	DIN EN ISO 13937-3	
	Warp	≥ 70 N
	Weft	≥ 270 N
Tensile strength	DIN EN ISO 13934-1	
	Warp	≥ 750 N
	Weft	≥ 960 N
Colour fastness to light	DIN EN ISO 105-B02	≥ 5 (blue scale)
Colour fastness to rubbing	DIN EN ISO 105-X12	
	Dry	4-5
	Wet	4-5
Resistance to pilling	EN ISO 12945-2	>4
Resistance to seam slippage	EN ISO 13936-2	
	Warp	ca. 1,0 mm
	Weft	ca. 1,0 mm
Snagging Test / Rotating Chamber Method	BS 8479	≥ 4
SAFETY		
Flame-retardant (UK)	BS 5852-1 EN 1021-1	Passed
Flame-retardant (US)	NFPA 260	Passed

VERSTEE

== LEATHER ==

COMPLIANCE

Reach	Free of harmful substances	Complies
Blue World		Complies