

VERSTEE

== LEATHER ==

TECHNISCHE FICHE

ARTIKELNAAM	RIGOR KUNSTLEDER
PRODUCTIE	DUITSLAND
ROLBREEDTE	137-140 CM
DIKTE	Ca 1,5 MM
ROLLENGTE	25 M

TEST	TEST METHOD	RESULT
PHYSICAL		
Weight		Ca. 930 gr/m ²
Composition	Coating	77% PVC compound
	Backing	23% Katoen
STRENGTH		
Martindale	DIN EN ISO 5470-2	≥400.000 cycles
Tear strength	DIN EN ISO 4674-1	
	Warp	≥ 30 N
Weft	≥ 40 N	
Tensile strength	DIN EN ISO 1421	
	Warp	≥ 400 N
Weft	≥ 350 N	
Adhesion	DIN EN ISO 2411	
	Warp	≥ 30 N/5 cm
Weft	≥ 30 N/5 cm	
Elongation	DIN EN ISO 1421	
	Warp	≥ 5%
Weft	≥ 20%	
Colour fastness to light	DIN EN ISO 105-B02	≥ 6 (blue scale)
Colour fastness to rubbing	DIN EN ISO 105-X12 Dry&Wet	4-5, 20 cycles
Colour fastness to bleach	DIN 54021	4-5 (grey scale)
Colour fastness to acid & alkaline	ISO 105-E04	≥4 grey scale)
Resistance to saliva	DIN 53160-1	≥4 grey scale)

VERSTEE

== LEATHER ==

STRENGTH		
Colour fastness to blood & urine		≥4 grey scale)
Colour fastness to ethyl alcohol (70%)	DIN 54021	4-5 (grey scale)
Colour to massage oil		4-5 (grey scale)
Resistance to temperatures	Cold crack	+/- 20°C tot +70°C
Resistance to alcohol <96%	ISO 25647	Passed
SAFETY		
Flame retardant UK	BS 5852, Crib 5 & EN 1021, 1&2	Passed
Flame retardant Automotive	FMVSS302	Passed
Flame retardant IMO	MSC,307 (88), Annex 1 Part 8	Passed
Flame retardant FR	NF P 95-503	M2
Flame retardant IT	UNI 9175	Class 1
Flame retardant US	NFPA 260	Passed
	CAL TB 117	Class 1
Flame retardant AT	Önorm A 3800-1 / B 3825	Passed
Resistance to bacteria	JIS Z 2801	Passed
Resistance to funghi	ISO 846	Passed
COMPLIANCE		
Reach	Free of harmful substances	Complies
Sanitized®		Complies
Animal Free®		Complies
Suitable for toys and children objects		Complies
Easy to clean with detergent		Complies